

Column 1 Systems and Components	Column 2 Minor Defects	Column 3 Major Defects
Part 1. Accessibility Devices	<i>Accessibility device may not be used if:</i> (a) alarm fails to operate. (b) equipment malfunctions. (c) interlock system malfunctions.	(a) vehicle fails to return to normal level after "kneeling". (b) extendable lift, ramp or other passenger-loading device fails to retract.
Part 2. Air Brake System	(a) audible air leak. (b) slow air pressure build-up rate.	(a) there is any indication of a brake adjustment problem. (b) air loss rate exceeds prescribed limit. (c) inoperative towing vehicle (tractor) protection system. (d) low air warning system fails or system is activated. (e) inoperative service, parking or emergency brake.
Part 3. Coupling Devices	(a) coupler or mounting has loose or missing fastener.	(a) coupler is insecure or movement exceeds prescribed limit. (b) coupling or locking mechanism is damaged or fails to lock. (c) defective, incorrect or missing safety chain or cable.
Part 4. Dangerous Goods	-	(a) dangerous goods requirements not met.
Part 5. Doors and Emergency Exits	(a) door, window or hatch fails to open or close securely. (b) alarm inoperative.	<i>(Passengers may not be carried <sup>1</sup>)</i> (a) required emergency exit fails to function as intended. _____ <sup>1</sup> vehicle may be moved when no passenger carried
Part 6. Driver Controls	(a) accelerator pedal, clutch, gauges, audible and visual indicators or instruments fail to function properly.	<i>(Passengers may not be carried <sup>2</sup>)</i> (a) accelerator sticking and engine fails to return to idle. _____ <sup>2</sup> vehicle may be moved when no passenger carried
Part 7. Driver Seat	(a) seat is damaged or fails to remain in set position.	(a) seatbelt or tether belt is insecure, missing or malfunctions.
Part 8. Emergency Equipment and Safety Devices	(a) emergency equipment is missing, damaged or defective.	-
Part 9. Exhaust System	(a) exhaust leak	(a) leak that causes exhaust gas to enter the occupant compartment.

Column 1 Systems and Components	Column 2 Minor Defects	Column 3 Major Defects
Part 10. Exterior Body	(a) insecure or missing body parts. (b) insecure or missing compartment door.	-
Part 11. Fuel System	-	(a) missing fuel tank cap <sup>1</sup> . (b) insecure fuel tank. (c) dripping fuel leak. _____ <sup>1</sup> vehicle may be moved when no passenger carried
Part 12. General	-	(a) serious damage or deterioration that is noticeable and may affect the vehicle's safe operation.
Part 13. Glass and Mirrors	(a) required mirror or window glass fails to provide the required view to the driver as a result of being cracked, broken, damaged, missing or maladjusted. (b) required mirror or glass has broken or damaged attachments onto vehicle body.	<i>(Passengers may not be carried <sup>2</sup>)</i> (a) driver's view of the road is obstructed in the area swept by the windshield wipers. _____ <sup>2</sup> vehicle may be moved when no passenger carried
Part 14. Heater / Defroster	(a) control or system failure.	(a) defroster fails to provide unobstructed view through the windshield.
Part 15. Horn	(a) vehicle has no operative horn.	-
Part 16. Lamps and Reflectors	(a) required interior lamp does not function as intended. (b) required reflector is missing or partially missing. (c) passenger safety or access lamp does not function.	<i>When lamps are required:</i> (a) failure of both low-beam headlamps. (b) failure of both rearmost tail lamps. <i>At all times:</i> (a) failure of a rearmost turn-indicator lamp. (b) failure of both rearmost brake lamps.
Part 17. Passenger Compartment	(a) stanchion padding is damaged. (b) damaged steps or floor. (c) insecure or damaged overhead luggage rack or compartment. (d) malfunction or absence of required passenger or mobility device restraints. (e) passenger seat is insecure.	<i>When affected position is occupied:</i> (a) malfunction or absence of required passenger or mobility device restraints. (b) passenger seat is insecure.

Column 1 Systems and Components	Column 2 Minor Defects	Column 3 Major Defects
Part 18. Steering	(a) steering wheel lash (free-play) is greater than normal.	(a) steering wheel is insecure, or does not respond normally. (b) steering wheel lash (free-play) exceeds prescribed limit.
Part 18. Suspension System	(a) air leak in air suspension system.	(a) damaged <sup>1</sup> or deflated air bag. ____ <sup>1</sup> patched, cut, bruised, cracked to braid, mounted insecurely
Part 20. Tires	(a) damaged tread or sidewall of tire. (b) tire leaking ( <u>if leak can be felt or heard, tire is to be treated as flat</u> )	(a) flat tire. (a. 1) tire leaking, if leak can be felt or heard. (b) tire tread depth is less than wear limit. (c) tire is in contact with another tire or any vehicle component other than mud-flap. (d) tire is marked "Not for highway use". (e) tire has exposed cords in the tread or outer sidewall area.
Part 21. Wheels, Hubs and Fasteners	(a) hub oil below minimum level (when fitted with sight glass). (b) leaking wheel seal.	(a) wheel has loose, missing or ineffective fastener. (b) damaged, cracked or broken wheel, rim or attaching part. (c) evidence of imminent wheel, hub or bearing failure.
Part 22. Windshield Wiper / Washer	(a) control or system malfunction. (b) wiper blade is damaged, missing or fails to adequately clear driver's field of vision.	<i>When use of wipers or washer is required:</i> (a) wiper or washer fails to adequately clear driver's field of vision in area swept by driver's side wiper.